

CODE	MODEL	TYPE	POWER SUPPLY	SERIES
10292002	M9TTG80	SOLID TOP	GAS	MILO 900

DESCRIPTION

GAS SOLID TOP**TECHNICAL DATA**

Gas power (kW)	13,9
N° of cooking zones	1X13,9kW
IPX Protection Grade (mm)	IPX4

DIMENSIONS DATA

Product dimensions (mm)	800W x 900 P x 290 H
Net weight (kg)	105
Gross weight (kg)	122
Packaging dimensions (m3)	845 x 972 x 624
Packaging volume (m3)	0.51

CONSTRUCTIONAL FEATURES

Worktop made of 2mm-thick AISI 304 stainless steel with Scotch Brite finish. Control panel, side panels and back panel in 1mm thick AISI 304 stainless steel with Scotch Brite finish. Precise juxtaposition of worktops ensuring maximum hygiene. Stainless steel brackets are provided as standard, allowing the appliances to be effectively fixed side by side (optional gasket). Sloping back guard, with built-in exhausted grate and removable steel closing grid. Adjustable feet with scratch-resistant sole made of insulating plastic material.

TECHNICAL FEATURES

Solid top with radiant plate in 15 mm thick alloy steel embedded in the worktop, surrounded by water-tight perimeter with large drain hole and GNI/3 molded collection tray, easily removable for emptying and cleaning operations. Different isothermal zones, starting from 500°C at the centre and then degrading near the edges. Heating obtained by stainless steel, cast-iron burners with continuous regulation by means of a valve tap with safety thermocouple. Piezo ignition of pilot flame. Central ring of 250mm diameter, removable for coup de feu or maintenance. Ergonomic, athermic control knob.

CODE

10292002

MODEL

M9TTG80

TYPE

SOLID TOP

POWER SUPPLY

GAS

SERIES

MILO 900

DESCRIPTION

GAS SOLID TOP**TECHNICAL DRAWING****CONNECTIONS**

G = GAS

1/2" G